



	Cap Press		Manual Press
Model	PHP-MC	PHP-GY	PHP-S
Type	Clamshell		Swing
Operation	Touch Screen		
Heating Size	3.5" x 5.0"	15" x 15"	14" x 15"
		16" x 20"	16" x 20"
		16" x 24"	



	Pneumatic Single Press
Model	PHP-P
Max Temp.	500°F
Thickness	40-70 mm
Stand	Optional
	14" x 15"
	16" x 20"
	24" x 32"
	32" x 40"



	Dual Heaters Press	Triple Heaters Press
Model	PHP-H2	PHP-H3
Max Temp.	500°F	
Thickness	40 mm	
Power	2.0 kw x 2	1.8 kw x 3
Heating Size	15" x 15"	16" x 20"
	16" x 20"	
	16" x 24"	
Apply to	double-sided heating, thicker labels, hotfix rhinestone application, embroidery labels with hot melt adhesive, silicone, etc.	



Full-Auto Dual Press

Model	PHP-AS
Heating Head Drop	Pneumatic Driven
Heating Head Shuttle	Pneumatic Driven
Stations	2
Plate	Changeable
Stand	Optional
Laser Positioning	Optional
Heating Size	14"x15" (360x380 mm)
	16"x20" (400x500 mm)
	20"x24" (500x600 mm)
	20"x28" (500x700 mm)
	24"x32" (600x800 mm)



Semi-Auto Dual Press

Model	PHP-A
Heating Head Drop	Pneumatic Driven
Heating Head Shuttle	Manual
Stations	2
Plate	Changeable
Stand	Optional
Laser Positioning	Optional
Heating Size	6"x6" (150x150 mm)
	14"x15" (360x380 mm)
	16"x20" (400x500 mm)
	20"x24" (500x600 mm)
	20"x28" (500x700 mm)
	24"x32" (600x800 mm)



Full-Auto 4-Station Press

Model	PHP-4050A4	PHP-4050A4-2	PHP-6080A4
Heating Head Drop	Pneumatic	Pneumatic	Pneu-hydraulic
Station Cycle	Electromotor	Electromotor	Electromotor
Heating Head	1	2	1
Stations	4	4	4
Power	3.3 Kw	6.0 Kw	12 Kw
Laser Positioning	Without		
Heating Size	16"x20" (400x500 mm)		24"x32" (600x800 mm)

Full-Auto 6-Station Press

Model	PHP-4050A6
Heating Head Drop	Pneumatic
Station Cycle	Electromotor
Heating Head	2
Stations	6
Power	6.0 Kw
Laser Positioning	Without
Heating Size	16"x20" (400x500 mm)

